

MULCHERS

LS7 SERIES



A range of mulchers with the following technical features and standard equipment:

- Suitable for machines from 10 to 25 Ton.
- Cutting width of 1300mm - 1600mm, suitable for cutting grass, brambles, hedges and forestry jobs up to 15 cm – forestry Ø 30 cm.
- Toothed, high-performance belt transmission.
- Internally reinforced with inside double-cased body with interspace.
- Shearing symmetric head, for effective operation with excavator rotation.
- Input and output mouths completely identical.
- Adjustable faceplates, fully openable for higher cutting capacity.
- Side skids adjustable with 3 positions to control cut height.
- Valves block complete with priority valve for adjusting oil flow, anti-shock valve (pressure relief valve), anti-cavitation.
- Rotor supports with internal labyrinth for bearing protection from impurities.
- Double row spherical adjustable bearings of premium quality.
- Motor protection guard - Safety guards rubber CE.
- Quick hitch mounting bracket available on demand.
- Pistons engine

OPTIONS:

- Hydraulic hoods



REVERSIBLE MODEL	DIGGER SIZE (Ton)	CUTTING WIDTH (mm)	WEIGHT (kg)	OIL REQ.	OIL PRESS (Bar)	TRANSMISSION	SIZE (cm)
LS7 1300 P	10 / 25	1300	650	100-125-160	200 - 350	Belt	160-80-85
LS7 1600 P	12 / 25	1600	750	100-125-160	200 – 350	Belt	190-80-85