MB-HDS314













1430 mm

SPECIFICATIONS

RECOMMENDED EXCAVATOR RECOMMENDED BACKHOE LOADER/	≥ 12 ≤ 20 ton
LOADER	$\ge 9 \le 14 \text{ ton }^*$ * Please verify machine's Rated Operating Capacity.
WEIGHT	1,40 ton
LOAD CAPACITY	0,90 m ³
PRESSURE	> 230 bar
OIL FLOW RATE	100 I/min. The hydraulic flow and pressure values must meet the required parameters.

SHAFT KITS

ACCESSORIES

RC COMPOST KIT

SHAFT HOLDER

RM MIXER KIT

•

•

• •

•

RQ20RQ50 SIFTING KIT

RE8/RE16 FINE SIFTING KIT

* shaft in closed position

KIT	ADJUSTMENT	APPLICATION
RQ20/RQ50 SIFTING KIT	20/50 mm	Sifting damp/dry soil Soil aeration
RM MIXER KIT	-	Soil Aeration Compost aeration Charcoal reduction Glass reduction Drywall reduction
RE8/RE16 FINE SIFTING KIT	8,5/16 mm	Sifting damp/dry soil
RC COMPOST KIT	36,5* mm	Shredding foliage and small nranches Composting

APPLICATION AREAS



The data provided above is not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.

ሪ

in f 🎔 🔿 🖓