MB-HDS320










1250 mm





2050 mm

ACCESSORIES

- RQ20/RQ50 SIFTING KIT
- RM MIXER KIT
- RE8/RE16 FINE SIFTING KIT
- RC COMPOST KIT
- SHAFT HOLDER

SPECIFICATIONS

RECOMMENDED EXCAVATOR RECOMMENDED BACKHOE LOADER /	≥ 18 ≤ 24 ton
LOADER	\geq 11 \leq 14 ton * * Please verify machine's Rated Operating Capacity.
WEIGHT	2,10 ton
LOAD CAPACITY	1,35 m ³
PRESSURE	> 250 bar
OIL FLOW RATE	120 I/min. The hydraulic flow and pressure values must meet the required parameters.

SHAFT KITS

* shaft in closed position

	KIT	ADJUSTMENT	APPLICATION
\Q	RQ20/RQ50 SIFTING KIT	20/50 mm	Sifting damp/dry soil Soil aeration
	RM MIXER KIT	-	Soil Aeration Compost aeration Charcoal reduction Glass reduction Drywall reduction
0	RE8/RE16 FINE SIFTING KIT	8,5/16 mm	Sifting damp/dry soil
Q	RC COMPOST KIT	36,5* mm	Shredding foliage and small nranches Composting

APPLICATION AREAS



















RECYCLING

UTILITY WORKS

COMPOSTING

INDUSTRIAL **AREAS**

ENVIRONMENTAL REMEDIATIONS

FINE SIFTING

URBAN CONSTRUCTION

AND CREATION
OF FOUNDATIONS

The data provided above is not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.











