



MB-G1200 S4



ACCESSORIES

- RECOMMENDED SPARE PARTS KIT
- FIXED COUPLING
- ROTATION POWER EXTENDER KIT (ROTATION FLOW RATE 40 ÷ 70 L/MIN)
- GRIP IMPROVEMENT KIT
- MULTI-PURPOSE BLADE KIT
- RUBBER PROTECTION KIT
- CLAM SHELL KIT
- 24 MONTHS WARRANTY

SPECIFICATIONS

RECOMMENDED EXCAVATOR	≥ 18 ≤ 30 ton
WEIGHT	1,65 ton
CAPACITY (CLAWS CLOSED)	0,71 m ³
ROTATION	360° Gradi
OIL PRESSURE (ROTATION)	> 220 bar
OIL FLOW RATE (ROTATION)	20 ÷ 35 l/min.
OIL PRESSURE (OPENING/CLOSING)	300 ÷ 400 bar
OIL FLOW RATE (OPENING/CLOSING)	70 l/min.

APPLICATION AREAS



URBAN
CONSTRUCTION
SITES



PORTS AND
FREIGHT
TERMINALS



QUARRIES



RECYCLING AND
WASTE SORTING
FACILITY



MOVING AND
SEPARATING
MATERIALS



UTILITY
WORK



LANDSCAPING

The data provided above is not binding, as the manufacturer reserves the right to make improvements to its products at any time and without notice.

Rev. 2022/11



MBCRUSHER.COM